

### **028.19 PRO HARLEY DRAGS (PHD)**

Pro Harley Drags –class motorcycle must be based on motorcycle powered by two cylinder pushrod –type engine with 45 degree cylinder angle. Aftermarket frames are permitted. Motorcycle doesn't need to be registered.

#### **028.19.1 Engine**

No restrictions.

Largest permitted displacement for naturally aspirated engines: 2100cc / 128cid.

Largest permitted displacement for turbocharged or nitrous oxide-powered engines: 1575cc / 96cid.

Only one power-adder permitted per bike (turbo and nitrous oxide systems together is prohibited)

#### **028.19.2 Transmission & Clutch**

Motorcycle must be able to start by original starter, all external starter systems prohibited.

Semi- and full automatic transmission are prohibited.

All types of semi- or automatic shifters are prohibited.

Ignition cut for shifts permitted.

#### **028.19.3 Frame**

Maximum wheelbase 1030mm, measured from middle of crankshaft to rear axle at it's rearmost point.

Steering stoppers required and they must enable min. 30 degree and max. 50 degree turns to both ways. Steering shock absorbers are prohibited to function as steering stoppers.

#### **028.19.4 Tires and wheels**

All tires must be road/street legal, also car tyres permitted.

Also max. 7" slick-tyre is permitted as rear tire.

#### **028.19.5 Wheelie Bars**

Prohibited.

#### **028.19.6 Oil catch can**

Oil catch can is mandatory equipment.

#### **028.19.7 Minimum weight**

Motorcycle minimum weight in race-ready condition: 180 kg.